



www.gasleaksensors.com

# SENS T<sup>®</sup> GOLD G2 VERSATILE MULTIPLE GAS DETECTION INSTRUMENT

# FIND GAS LEAKS FASTER

**SENSIT**<sup>®</sup> **GOLD G2** is the most versatile and user-friendly SENSIT available. The "G2" can be configured for combustible gas readings in PPM, LEL and/or percent volume, as well as a variety of toxic sensors and oxygen. The SENSIT GOLD G2 is ideal for leak location and confined space applications.

## **Displays Up To 4 Gases Simultaneously**

- LEL (%Volume and PPM Optional)
- Oxygen
- Carbon Monoxide
- Hydrogen Sulfide
- Hydrogen Cyanide (Optional)

## Selectable Gas Type

- Methane (Natural Gas)
- Propane

## **G2 Standard Features**

- Internal Pump Fast Sampling
- Digital "Tick" Control Fast Leak Location
- Lowest Cost, Long Life Sensors
- LED Warning Lights
- Bright Graphic Display
- Loud Audible Alarm
- Battery Strength Indicator
- Internal Memory
- Exceptional Water Protection



#### INDUSTRY USERS

Gas Companies (natural & propane) Gas Exploration & Transmission COs Industrial Plants Chemical/Petro Chemical Plants Fire - Hazmat - Arson Services HVAC Contractors



## APPLICATIONS

Combustible Gas Leak Detection Gas Leak Survey Underground Leak Pinpointing Carbon Monoxide Investigations Confined Space Monitoring Combustible Gas Measurements Pipeline Purging



PARTIAL LIST OF GASES SENSED\*

Butane Carbon Monoxide Gasoline Hydrogen Sulfide Methane Natural Gas Oxygen Propane



## SENSOR SPECIFICATIONS

ТҮРЕ	RESOLUTION	RANGE	ACCURACY
PPM*	1ppm or 10ppm	0-2,000 ppm	±10%
LEL	0.1% up to 2%	0-100% LEL	±10%
% NAT GAS	0.1%	5-100% GAS	±5%
% propane	0.1%	2.2-100% GAS	±5%
02	0.1%	0-25%	±0.2% or 2%**
СО	lppm	0-2000ppm	±5ppm or 5%**
H2S	lppm	0-100ppm	±2ppm or 5%**
HCN	lppm	0-30ppm	±5%
*PPM Optional			**Whichever is greater

#### **PRODUCT SPECIFICATIONS**

Size:	11.5" x 3" x 2.32" (29.2 x 7.6 x 5.9 cm)
Weight:	1.2 lb. (544 g)
Operational Temp:	-4 to 104 F (-20 to 40° C)
Battery Life:	Alkaline: Approximately 13 hrs. Continuous



#### **STANDARD KIT**

Wrist Strap Hard Carrying Case 3 "C" Batteries T10 Allen Wrench Extra Sensor Cap Instruction Manual Choice of 2 Piece Bar Hole Probe or Confined Space Probe

#### **OPTIONAL FEATURES**

**Data Logging Options:** 100 Instant Event Saves 1600 Auto Log Saves 100 Bar Hole Tests

#### **ADDITIONAL FEATURES**

**Bar Hole Test Features:** Peak Readings Sustained Readings Timed Test

### **Adjustable Calibration Reminders:**

Calibration Due Calibration Over-Due (Shows at Start-up)

**Adjustable Gas Scales:** Auto Range Point for LEL to %Vol

**Gas Identification Alert Options:** "NSR" - Non-Combustible Gas Sensed "NSC" - Combustible Other Than Gas Calibrated to (4-5% Volume)

ATEX Cert. No. TRAC11ATEX21304X



Ex ib IIB T3 AEx ia IIB T3 IP54

CERTIFICATE ISSUED BY:



US Listed UL 913

Intrinsically Safe for Use in Class I, Groups C and D, T3 Hazardous Locations

#### SENSIT GOLD G2 ACCESSORIES (LEL) $(PPM^* + LEL)$

SMART-CAL Auto Calibration Station Only Part #914-00000-01

SMART-Cal Standard Gas Kit 221 Liter (Not for use with H2S, Propane or 100% CH4) Part # 881-00045

Smart-Cal 58 liter H2S Cal Kit only Part # 881-00047

#### Manual Calibration Kits are available. Please contact factory for price and part number.

21 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-080021

103 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-140001

221 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-180028

21 liter 1.1% Propane/Air Part # 315-080022

58 liter Hydrogen Sulfide (25ppm H2S/Air) Part # 315-120001

Sensor Cap (Replacement) w/"O" Rings Part # 870-00018

Extension Adapter Part # 870-00012

Hot Air Probe Part # 883-00023

**Confined Space Probe** Part # 883-00015

PC Interface with Software Part # 870-00008

Printer (Infrared) Part # 870-00004

Wrench (Battery Compartment Tool) Part # 360-00105



851 Transport Drive Valparaiso, IN 46383-8432

Phone: 888 4SENSIT 888 473 6748 219 465 2700

Fax: 219 465 2701 www.gasleaksensors.com MADE IN USA

**SENSIT** Technologies is in compliance with ISO 9001:2008





#### Form # BGOLDG2-IS01-ATEX © 2011 SENSIT TECHNOLOGIES

ISSUED: 12-6-2010

#### REV: 10-4-2011

#### The following accessories to be used with the SENSIT GOLD G2 (LEL + % V/V) $(PPM^* + LEL + \% V/V)$

21 liter 100% Methane Part # 315-080007

Demand Regulator – Use with Line Gas Part # 880-00007

2pc Probe Assembly Part # 883-00036

30" Brass Probe (5/16 OD) Part # 883-00018

32" Fiberalass Probe Part # 883-00019

Purge Probe (Brass) Part # 883-00030

Plunger Bar 42" Part # 870-00010

Hydrocarbon Filter Kit (6 pack) Part # 873-00015

Inline "Mini" Hydrocarbon Filter Kit (10 pack - BH probe with filter required) Part # 873-00012

\*PPM Optional

For more information, visit www.gasleaksensors.com

Distributed by:

