

Transmitter EC28 Di

for toxic gases, oxygen and hydrogen



- Gas concentration reading at transmitter display
- ATEX certified Ex II 1 G EEx ia IIC T4
- One-man calibration at transmitter via touch keys or remote control
- Plug-in Smart Sensor
- Sensor replacement without opening housing
- Intrinsically safe

Worldwide Supplier Of Gas Detection Solutions



Transmitter EC28 Di

Superior technology

Wherever gas hazards are to be expected, the transmitter EC28 Di and GfG's proven control systems are the right choice for reliable surveillance. The ATEX-certified design provides the highest safety even in hazardous areas. LED indicate operation (green) or fault (red).

The transmitter EC28 Di reads the current gas concentration at site on the display with a four-digit LCD for measurement values, messages and service. Calibration and function tests are done directly with three touch keys under the transmitter display. It complies with the highest safety requirements with certified intrinsic safety.

Smart sensors

The Smart sensor technology allows the user to install the transmitter or to replace a sensor within a few seconds – just plug the sensor into the transmitter. Adjustments are done directly at the transmitter via touch keys or with the remote control (one man calibration).

Remote Control RC2

Ammonia and hydrogen are lighter than air. With the transmitter installed close to the ceiling you can provide permanently connected cable with plugs for the remote control, which allows the user to do all adjustments without having

to climb a ladder. One remote control can be used for several transmitters. The remote control always shows the same reading as the transmitter. The remote control simplifies inspection, service and calibration considerably. In addition to this, the remote control reads the current gas concentration and can be used as an external display.

Reliable detection and minimized cost of ownership

The sensor and integrated temperature compensation provide highest measurement accuracy. Low maintenance requirements and long sensor life reduce your cost of ownership.

Versions

EC28 basic unit without display.

EC28 D with display of actual gas concentration.

EC28 DA with display, bright alarm LED and integrated buzzer. No need for an expensive Ex-proof buzzer means less wiring costs.

EC28 DAR includes a relay for additional external alarm devices.

EC28 B with BUS-interface.

EC28 DB with BUS-interface and display of actual gas concentration.

EC28 DAB with BUS-interface and display of actual gas concentration, with bright alarm LED and integrated buzzer. No need for an expensive Ex-proof buzzer means less wiring costs.

EC28 i intrinsically safe model.



RC2 with EC28 DA

In combination with GfG's flexible controllers the transmitter EC28 provides many possibilities for reliable and cost effective monitoring toxic gases.

Advantages at a glance

- ATEX-approval
- Plug-in smart sensor for easy sensor replacement
- Long sensor life
- Low service requirement
- Permanent function display
- Calibration without opening housing
- Intrinsically safe

Transmitter EC28 Di Technical Data

Detection principle:

Electrochemical sensor

Ambient temperature:

-20°C .. +50°C

Output signal:

4 – 20 mA

Supply voltage:

15 – 30 V DC

Weight:

800 g with display

Dimensions:

100x193x55 mm (WxHxD)

Casing protection:

IP64

ATEX labelling:

Ex II 1 G EEx ia IIC T4

CE 0158

Touch keys:

3 keys for all adjustments / calibration, function test

Display:

4-digit LCD for linearized measurement values and messages, service, LED for operation / fault

Transmitter cable:

Shielded cable
2/3/6 x 0.75mm²
M 16 x 1,5

Gases and Detection Ranges (ppm)

All detection ranges are scalable - except HF and O₃ (0 - 1 ppm)

Ammonia NH ₃	Chlorine Cl ₂	Chlorine dioxide ClO ₂	Hydrogen chloride HCl	Hydro cyanide HCN	Ethylene oxide C ₂ H ₄ O	Hydrogen fluoride HF	Carbon monoxide CO
0 - 200 0 - 500 0 - 1000	0 - 50 0 - 250	0 - 2	0 - 30 0 - 200	0 - 50 0 - 200	0 - 100	0 - 10	0 - 500 0 - 2000

Ozone O ₃	Phosgene COCl ₂	Oxygen O ₂	Sulphur dioxide SO ₂	Hydrogen sulphide H ₂ S	Silane SiH ₄	Nitrogen dioxide NO ₂	Nitrogen monoxide NO	Hydrogen H ₂
0 - 1 0 - 5	0 - 2	0 - 30 Vol.-%	0 - 50 0 - 500	0 - 200 0 - 1000	0 - 50	0 - 50 0 - 200	0 - 300 0 - 1500	0 - 2000 0 - 1 Vol.-% 0 - 4 Vol.-%



GfG Headquarters
Klönnestrasse 99
44143 Dortmund • Germany
Phone: +49 / (0)231 - 564 000
info@gfg.com • www.gasmessung.de

GfG Europe
Great Dunmow
Essex CM6 1XG • United Kingdom
Phone: +44 / (0)1371 - 874 447 • Fax: +44 / (0)1371 - 879 904
info@gfgeurope.com • www.gfgeurope.com